

**High Speed & Compact 24-Pin Narrow Carriage Impact Printer**  
for medium & large print volume



# DP350

High Speed & Compact 24-Pin  
Narrow Carriage Impact Printer

### Highlights:

- Fast printing speed of up to 400 characters per second
- Better connectivity with Standard Parallel & USB 2.0 Interfaces
- Optional Serial, Ethernet & additional USB Interfaces
- Optimum efficiency with 5-pay forms printout (Original + 4 Copies)
- Trustworthy printhead (500 million strokes)
- Choice of 9 built-in bar code formats for maximum versatility

# DP350

High Speed & Compact 24-Pin Narrow Carriage Impact Printer



## Specification:

|                 |  |
|-----------------|--|
| Print type      | 24-pin impact dot matrix   |
| Print direction | Bi-directional with logic seeking  |
| Print width     | 80 Columns (10CPI) / 203.2mm   |
| Print speed     | Super high speed 400 CPS<br>High speed 300 CPS<br>Normal 150 CPS   |
| Print head      | Diameter of wire: 0.22mm,<br>Life: 500 million strokes/wire  |
| Resolution      | 360×360 DPI (Maximum)  |
| Character sets  | 17 international character sets<br>U.S.A, France, Germany, U.K, Denmark1,<br>Sweden, Italy, Spain1, Japan, Norway,<br>Denmark2, Spain2, Latin Am, Korea, Legal,<br>Netherlands, Turkey |
| Fonts           | Draft, Roman, Sans Serif, Courier, Prestige,<br>Script, OCR-A, OCR-B, Orator   |
| Bar code        | EAN-13, EAN-8, Interleaved 2 of 5,<br>Matrix 2 of 5, Industrial 2 of 5, Code 39,<br>Code 128 B, Code 128 C, NW-7   |
| Character pitch | 10CPI, 12CPI, 15CPI, proportional  |
| Line space      | 1/6 inch, 1/8 inch, programmable in 1/360 inch<br>increments   |
| Emulation       | EPSON ESC/PK2, IBM 2391  |
| Interface       |  |
| Standard        | Bi-directional parallel interface (IEEE-1284<br>nibble mode),<br>First USB 2.0 (Full- Speed) interface,  |
| Options         | Second USB 2.0 (Full- Speed) interface,<br>10/100 Base-T Ethernet interface,<br>RS-232C serial interface   |
| Buffer Memory   | 132KB  |
| Ribbon          |  |
| Model           | JMR120   |
| Life            | > 10 million characters (draft mode)   |
| Noise           | <53dB(A)(ISO7779 standard)   |

Jolimark DP350 is a fast, small & heavy duty machine which is ideal for dealing with huge printing demand in hospitals, hotels, retail stores, hospitality industries.

|                          |  |
|--------------------------|--|
| Paper feed type          |  |
| Cut sheet                | Feed paper by friction   |
| Continuous paper         | rear in ,front out   |
| Paper specification      |  |
| Cut sheet                | Width: 48~261mm,<br>Thickness: 0.065~0.14mm,<br>Weight: 52~90 g/m <sup>2</sup>   |
| Continuous paper         | Width: 56~267mm, Thickness: 0.065~0.39mm,<br>Weight: Single sheet: 52~82 g/m <sup>2</sup> ,<br>Multiple part: Every page40~58 g/m <sup>2</sup> |
| Max paper thickness      | 0.52mm   |
| Copy                     | Original+4 copies  |
| Automatic function       |  |
| Options                  | Automatic paper edge detection,<br>Black mark detection  |
| Compress set             | Compressed printing for character and graphics   |
| Special function         | Automatic Pin Break Compensation,<br>Automatic Pin Alternation,<br>Automatic Emulation Match,<br>Online Parameter Setting                      |
| Dimension                | 384mm(W) × 280mm(D) × 139mm(H)   |
| Weight                   | Approx. 6Kg  |
| Environmental conditions |  |
| Operating                | Temperature: 5~40°C,<br>Humidity: 40%RH~90%RH(No condensation)   |
| Storage                  | Temperature: -40~55°C,<br>Humidity: ≤93%RH(40°C, No condensation)  |
| Power requirements       | Rated voltage: 176~242V or 100~110V,<br>Rated frequency range: 50~60Hz   |
| Safety marks             | GB4943 / EN60950   |
| Certificate              |  |



DNVISO14001



BSI  
FME3174 ISO9001



OHSAS 18001



EN60950

\*The specifications above are subject to be changed without notice.

**Jolimark**<sup>®</sup>

Address: Unit 01, 23A/F, K.Wah Centre, 191 Java Road, North Point, Hong Kong

Tel: (852) 25582457

Fax: (852) 28979610

Email: sales@kongyue.com.hk

Http://www.jolimark.com/en