

*Compact & Cost-effective 24-Pin Narrow Carriage Impact Printer*



**DP350+**

- 24-pin Dot Matrix
- Fast printing sepped: 440CPS
- Better connectivity with:  
Standard USB + Parallel Interface  
Optional Second USB, Ethernet or  
Serial Interfaces
- Original + 4 Copies



# Compact & Cost-effective 24-Pin Narrow Carriage Impact Printer



**DP350+**

**Specification:**

Print type	24-pin impact dot matrix
Print direction	Bi-directional with logic seeking
Print width	80 Columns (10CPI) / 203.2mm
Print speed(10CPI)	Super high speed 440 CPS High speed 300 CPS Normal speed 150 CPS LQ speed 100 CPS
Fonts	Draft, Roman, Sans Serif, Courier, Prestige, Script, OCR-B, OCR-A, Orator
Bar code	EAN-13, EAN-8, Interleaved 2 of 5, matrix 2 of 5, industry 2 of 5, code 39, code 128 B, code 128 C, NW-7
Character pitch	10CPI, 12CPI, 15CPI, proportional
Line space	1/6 inch, 1/8 inch, programmable in 1/360 inch increments
Emulation	EPSON ESC/PK2, IBM 2391
Interface	DP350+ <b>U P</b> DP350+(S) <b>U P S</b> DP350+(E) <b>U P E</b> DP350+(U) <b>U U P</b> DP350+(US) <b>U U P S</b> DP350+(UE) <b>U U P E</b>
Buffer Memory	256 KB
Ribbon Model Life (draft mode)	JMR141 > 10 million characters
Noise	< 57 dB(A) (ISO7779 standard)
Paper feed type Cut sheet Tractor paper	Feed paper by friction Feed paper by drive tractor
Paper specification Cut sheet Tractor paper	Width: 48 ~ 261 mm Width: 56 ~ 267 mm
Max paper thickness	0.52 mm
Copy	Original + 4 copies
function	
Automatic paper edge detection	Optional
Black mark detection	Optional
Automatic Pin Break Compensation	√
Automatic Pin Alternation	√
Automatic Emulation Match	√
Online Parameter Setting	√
Dimension (W×D×H)	384mm × 280mm × 139mm
Weight	Approx. 6Kg
Environmental conditions Operating Storage	Temperature: 5 ~ 35 C, Humidity: 25 ~ 80%RH (No condensation) Temperature: -40 ~ 55 C, Humidity: ≤93%RH ( 40 C, No condensation)
Power requirements Rated voltage Rated frequency range	220 V(AC) 50Hz ~ 60Hz

Note: 1. The technical specifications in this catalog are the laboratory measurement data which achieved under the national standard for the storage and work environment (room temperature), the specifications of the testing papers are specified in the Users' Manual.  
 2. The technical specifications are subject to change without notice.  
 3. All trademarks are the properties of their respective holders.



Address: Unit 07, 21/Floor, K. Wah Centre, 191 Java Road, North Point, Hong Kong  
 Tel: (852) 25582457 Fax: (852) 28979610  
 Email: sales@kongyue.com.hk Http://www.jolimark.com/en

