

## High Speed & Versatile 24-Pin Wide Carriage Flatbed Impact Printer for handling wide range of paper size & thickness



# FP-8800K+

High Speed & Versatile 24-Pin  
Wide Carriage Flatbed Impact Printer

### Highlights:

- Fast printing speed of up to 400 characters per second
- Better connectivity with USB 2.0 & Standard Parallel, Optional Ethernet & Serial Interfaces
- Optimum efficiency with 7-ply forms printout (Original + 6 Copies)
- Trustworthy printhead (500 million strokes)
- Choice of 9 built-in bar code formats for maximum versatility

# FP-8800K+





High Speed & Versatile 24-Pin Wide Carriage Flatbed Impact Printer



## Specification:

Print type	24-pin impact dot matrix
Print direction	Bi-directional with logic seeking
Print width	136 Columns (10CPI) / 345.44mm
Print speed	Super high speed 400 CPS High speed 300 CPS Normal 200 CPS High density 150 CPS
Print head	Diameter of wire: 0.22mm, Life: 500 million strokes/wire
Resolution	360×360 DPI (Maximum)
Character sets	17 international character sets U.S.A, France, Germany, U.K, Denmark1, Sweden, Italy, Spain1, Japan, Norway, Denmark2, Spain2, Latin Am, Korea, Legal, Netherlands, Turkey
Fonts	Draft, Roman, Sans Serif, Courier, Prestige, Script, OCR-A, OCR-B
Bar code	EAN-13, EAN-8, Interleaved 2 of 5, Matrix 2 of 5, Industrial 2 of 5, Code 39, Code 128 B, Code 128 C,NW-7
Character pitch	10CPI, 12CPI, 15CPI, proportional
Line space	1/6 inch, 1/8 inch, 1/360 inch
Emulation	EPSON ESC/PSK2, OKI5530SC, IBM 2391
Interface	
Standard	USB 2.0 ( Full-Speed ) interface, Bi-directional parallel interface (IEEE-1284 nibble mode)
Options	RS-232C serial interface, 10/100 Base-T Ethernet interface
Input Buffer	132KB
Ribbon	
Model	JMR106
Life	> 20 million characters (draft mode)
Noise	<58dB(A)(ISO7779 standard)

Jolimark FP-8800K+ is of high speed & durability to handle the relentless daily printing demands of everywhere from banks to freight forwarders. It can handle wide range of paper size & thickness to meet the needs of all business sectors.

Paper feed type	
Cut sheet	front in, front out
Continuous paper	rear in, front out
Paper specification	
Cut sheet	Width: 127~430mm, Length: 127~558.8mm, Thickness: 0.08~0.12mm, Weight: 60~105 g/m <sup>2</sup>
Continuous paper	Width: 127~406mm, Thickness: 0.08~0.12mm, Weight: Single sheet: 60~10g/m <sup>2</sup> , Multiple part: Every page40 g/m <sup>2</sup>
Max paper thickness	2.0mm
Copy capability	Original+6 copies
Automatic function	Automatic gap adjustment, Automatic document alignment, Automatic paper edge detection
Special function	LCD display
Dimension	635mm(W) × 335mm(D) × 294mm(H)
Weight	Approx. 22Kg
Environmental conditions	
Operating	Temperature: 5~40°C, Humidity: 40%RH~90%RH(No condensation)
Storage	Temperature: -40~55°C, Humidity: 93%RH(40°C, No condensation)
Power requirements	Rated voltage: 198~242V or 100~110V, Rated frequency range: 50~60Hz
Safety marks	GB4943 / EN60950
Certificate	
	   
	DNVISO14001      BSISO9001      OHSAS 18001      EN60950

\*The specifications above are subject to be changed without notice.

**Jolimark®**

Address: Unit 01, 23A/F, K.Wah Centre, 191 Java Road, North Point, Hong Kong  
Tel: (852) 25582457 Fax: (852) 28979610  
Email: sales@kongyue.com.hk Http://www.jolimark.com/en