

*Compact & Cost-effective Impact Receipt Printer
offering easy-to-use solution to the retail and hospitality industries*



Tax control >>



Restaurants >>



Retail >>

TP200

Compact & Cost-effective Impact Receipt Printer



Highlights:

- Fast printing speed of up to 4.6 lines per second
- Various interface selections with Serial, Parallel, USB 2.0, Ethernet, Bluetooth, WiFi
- Optimum efficiency with 3-pay forms printout (Original + 2 Copies)

TP200 Compact & Cost-effective Impact Receipt Printer



User-friendly Design



Media/Ribbon Installation



Media Usage Monitoring Window

Item	Description
Printing method	9 Pins Dot matrix impact
Printing direction	Bidirectional logic seeking
Diameter of wire	0.3 mm
Dot density	160×144DPI (maximum)
Print speed	4.6 lines per second (paper width 76 mm, 40 columns)
Copy	Original + 2 copies
Effective printing width	63 mm (paper width 76 mm), 45 mm (paper width 57 mm)
Paper feed speed	Max:135 mm/s
Line spacing	et by the increment of 1/6 inch or 1/144 inch
Control panel	Touch keys operation, 2 keys and 3 LED indicators
Paper Specification	Roll paper model
	Common single-sheet roll paper Common two-sheet, trilogy roll copy paper
	Width: 57.5 ±0.5 mm, 76 ±0.5 mm Weight: 52.3 ~ 64.0 g/m2 Maximum diameter: Φ83 mm Paper thickness: 0.06 ~ 0.20 mm
	Note: The inner diameter of paper shaft is Φ12 mm and the outer diameter of paper shaft is Φ18 mm.
Character set	ASCII character set, International character set
Ribbon	Type: JMR112 Life: 3 million characters

Interface

This printer can be equipped with the following interfaces
 Parallel interface: Centronics
 USB interface: 2.0 Full-Speed
 USB interface (2.0 Full-Speed) + Serial interface (RS-232C, DB9)
 USB interface (2.0 Full-Speed) + Ethernet interface (10/100Base-T)
 USB interface (2.0 Full-Speed) + Serial interface (RS-232C, DB9)
 + Ethernet interface (10/100Base-T)
 Bluetooth interface
 Wi-Fi (802.11b/g/n) interface
 Serial+Ethernet+USB interface



**Note: 1. Only one of the data interfaces is supplied when leaving the factory.
2. Please take the specific interface as standard.**

Item	Description
Cash drawer interface	RJ-11, 24V(DC)/1A
Black mark	Optional
Special function	Touch keys, Online parameter settings, Software online upgrade
Input buffer	6 KB
Control command	ESC/POS Emulation
	Character printing command: Support ANK characters, user-defined characters and enlarged printing of Chinese characters 1-2 times, can adjust character line spacing
Power Supply (AC adapter)	Input
	Output
Power input	Parameters
	Warning: Please use the original AC adapter only. Manufacturers have no responsibilities for the problems which are led by using unauthorized AC adapter.
Environmental conditions	Operating environment
	Storage environment
Weight	Approx.1.2 Kg
Noise	<58 dB (A) (SO7779 standard)
Physical dimensions	154 (width) × 210 (depth) × 132 mm (height)
Resolution	Horizontal
	Vertical: 144 DPI
Power consumption	1. Operating: 40 W; 2. Standby: Approximately 1.5 W
	Note: Only when the product is unconnected with outer power supply, can it achieve zero energy consumption.

Certificate



DNVISO 14001



BSISO9001



OHSAS 18001

*The specifications above are subject to be changed without notice.

Jolimark®

Address: Unit 01, 23A/F, K.Wah Centre, 191 Java Road, North Point, Hong Kong

Tel: (852) 25582457

Fax: (852) 28979610

Email: sales@kongyue.com.hk

Http://www.jolimark.com/en