

*High Speed & High Performance Thermal Receipt Printer
ideal for supermarket, restaurant & lottery industries*



Supermarkets >>




Restaurants >>



Lottery >>

TP510



Thermal Printer

High Speed & High Performance Thermal Receipt Printer



Highlights:

- Fast printing speed of up to 100mm per second
- Various interface selections with Serial, Parallel, USB 2.0, Ethernet, Bluetooth, WiFi
- Trustworthy printhead (5 million lines)
- Easy paper loading





Widely used in bill printing in lottery, supermarkets, restaurants and chain stores.etc



Paper Easy loading



Easy Operation

Specification:

Print type	Thermal line printing
Print width	48mm / 384 dots (paper width 57.5±0.5mm)
Print speed	100mm/second
Print head	Life: 50km
Resolution	203×203 DPI (Maximum)
Character sets	16 international character sets
Bar code	UPC-A, UPC-E, EAN13, EAN8, Code 39, Interleaved 2 of 5, Codabar, Code 128
Line space	1/6 inch, programmable in 1/203 inch increments
Emulation	EPSON ESC/POS
Interface	RS-232C serial interface + USB interface or 10/100 Base-T Ethernet interface + USB interface or Bi-directional parallel interface (IEEE-1284 nibble mode) or USB 2.0 (Full-Speed) interface or Bluetooth (2.0/2.1+EDR) interface Wi-Fi interface Serial+Ethernet+USB interface



Input Buffer	2KB or 6KB (Ethernet interface version)
Noise	<50dB(A)(ISO7779 standard)
Paper feed type	Feed paper by friction
Paper specification	Width: 57.5mm± 0.5 mm, Weight: 53~60g/m ² , Roll Diameter: 83mm(Maximum)
Max paper thickness	0.065-0.15mm

Special function	Online Parameter Setting
Dimension	120mm(W) × 192mm(D) × 130mm(H)
Weight	Approx. 850g

Environmental conditions	
Operating	Temperature: 0~50°C, Humidity: 20%RH~85%RH (No condensation)
Storage	Temperature: -20~60°C, Humidity: 5%RH~95%RH (No condensation)

Power requirements	
Input	Rated voltage: 100~240V, Rated frequency range: 50~60Hz
Output	Rated Voltage: DC8.5V, Rated Current: 3A

Reliability	
MCBF	> 5 million lines

Certificate	
-------------	--



DNVISO14001



BSIISO9001



OHSAS 18001

*The specifications above are subject to be changed without notice.